

series
T|TB|TF|TP

Cam switches

Cam switches available in different construction models over a wide current range with a large variety of accessories.

series
T



From 12A up to 1200A
(under request).
1P up to 12P.
Four sizes available: 0, 1, 2, 3
Supplied with IP20
removable terminals
protection (except T175).
Wide range of devices and
accessories.

series
TB



From 20A up to 32A.
1P up to 12P.
Side access to all terminal
screws (up and down).
Two different bodies
depending on mounting
type: door or base
mounting.
Wide range of devices and
accessories.

series
TF



From 12A up to 32A.
1P up to 12P.
Square body, smooth sides,
axial access to terminal
screws.
Two different bodies
depending on mounting
type: door or base
mounting.
Wide range of devices and
accessories.

series
TP



Available for 12A.
1P up to 12P.
Reduce-sized body.
Door mounting only.
Wide range of devices and
accessories.

series|type
T|P



Cam switch in plastic
enclosure for gland entry.
From 12 up to 40 A.
Padlockable handle under
request.

series|type
T-TF|R



Cam switch in plastic
enclosure for gland entry.
From 25 up to 100 A.
Padlockable handle under
request.

series|type
T-TB|A-C



Cam switch in metal
enclosure of cast
aluminium.
From 12 up to 63 A.
In sheet steel enclosure
from 100 A upwards.
Gland entry.
Several enclosure sizes.
Padlockable handle under
request.

**Customized
solutions**



From 10A up to 1200A.
Any electrical programme
can be executed.
Up to 36 positions and 72
contacts.
Reversing, selector,
ammeter, voltmeter...

>> Ask for more information about these applications with enclosure.

series
ZBK

AC Modular switch - disconnectors and changeover switches

Modular switch – disconnectors and changeover switches of reduced size, available in different fixation types with a wide range of currents and a variety of accessories.

series
ZBK O-I

3P or 3P+N.
From 10A up to 125A.
Door mounting fixing by screws.
Two sizes of padlockable handles.
Auxiliary terminals and other accessories.



From 3P (20A-125A) up to 8P (25A-80A).
Base mounting fixing by screws or DIN rail and handle $\varnothing 22$.
Two sizes of padlockable handles.
Shaft extension depth adjustable.



From 3P (20A-125A) up to 8P (25A-80A).
Base mounting fixing by screws or DIN rail.
Direct handle (modular) with lock.
Auxiliary terminals and other accessories.

series
ZBK I-O-II

Switches from 3P up to 8P or changeovers.
Modular switch in plastic enclosure (sealable).
Padlockable handles.



3P+N. From 20A up to 63A.
Base mounting fixing by screws or DIN rail.
Direct handle (modular) with lock.
Supplied with bridging links included.
Auxiliary terminals and other accessories.